

Xerox® Phaser® 3155 / 3160 Black and White Printer

Print efficiency on a budget.

Get the printing power to meet the everyday demands of a busy single user or an entire workteam. Compact and capable, the Xerox® Phaser 3155 / 3160 delivers all-purpose printing at a very affordable price.



Empower your office.

- Print speeds of up to 24 ppm (A4) – plus a fast first-page-out time – keeps pace with your workload.
- Crisp 600 x 600 dpi and up to 1200 x 1200 (Phaser 3160) and 1200 x 600 (Phaser 3155) enhanced image quality.
- Easily connect one user or your entire workteam. The Phaser 3160N comes with Ethernet and USB, standard, and is fully network ready. Or choose the Phaser 3155 or Phaser 3160B and connect via USB.
- Xerox® CentreWare® Internet Services lets you check job status and manage your networked Phaser 3160N printer from anywhere using a web browser.
- Tackle more projects with a range of features including watermark*, overlays*, poster and booklet (manual) modes*.
- Robust design and high duty cycle for trouble-free dependability.

Surprisingly low cost.

- Get more for less with superior laser performance at an entry level price.
- Save paper by using manual two-sided printing feature* and the ability to print multiple pages on a single sheet of paper (N-up).
- Choose long-lasting high-capacity toner cartridges to lower your cost per print and use Toner Saver mode to extend consumables even further. Job Cancel feature lets you avoid printing unwanted pages.

Just the right fit.

- Compact design sits comfortably on your desktop or small workspace.
- Very quiet operation minimises impact in small offices.
- Print in various environments including Windows, Linux and Macintosh.
- Phaser 3160N supports IPv6 and SNMPv3 to ensure that your networked printer stays secure.
- Generous paper capacity of 250 sheets means fewer interruptions to reload paper. The enclosed paper tray keeps the printer's footprint small, and paper clean.
- A single-sheet multipurpose tray allows feeding of special sizes and types of media, like envelopes, transparencies and postcards.

*Windows only

- Print
- A4
- 24 ppm



WxDxH:
360 x 389 x 230 mm



Xerox® Phaser® 3155 / 3160

Black and White Printer



	Phaser® 3155	Phaser® 3160B	Phaser® 3160N
Speed	Up to 24 ppm A4		
Duty Cycle	Up to 12,000 pages / month	Up to 15,000 pages / month	
Paper Handling	Main Tray: 250 sheets; Sizes: A4, A5 Multipurpose Tray: 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm		
Paper Input			
Paper Output	80 sheets		
Two-sided Output	Manual		
Print			
First-page-out Time	As fast as 8 seconds		
Resolution	600 x 600 dpi, up to 1200 x 600 enhanced image quality	600 x 600 dpi, up to 1200 x 1200 enhanced image quality	
Processor	150 MHz	360 MHz	
Memory (std/max)	8 MB	64 MB	
Connectivity	USB 2.0		USB 2.0, 10/100 Base-TX Ethernet, IPV6, IPV4
Language Support	GDI	PCL®6/PCL5e, Epson/IBM, GDI	
Print Features	Watermarks*, Poster printing*, N-up, Fit to page, Scaling, Overlays*, Booklets* (manual), Reduce/enlarge, Toner saver, Custom-size pages		
Warranty	One-year warranty		

*Windows only

Device Management

All models: Status Monitor*; Phaser 3160B/N: Printer Settings Utility; Phaser 3160N: Xerox® CentreWare® IS Embedded Web Server, CentreWare Web, Xerox® Global Print Driver

Print Drivers

Windows® 2000/XP/2003 Server/2008 Server, Vista, Mac OS®X version 10.3-10.6, Various Linux® OS including RedHat Enterprise Linux WS 4, 5 (32/64bit), Fedora Core 2-10 (32/64bit), SuSE Linux 9.1 (32bit), OpenSuSE 9.2, 9.3, 10.0, 10.1, 10.2, 10.3, 11.0, 11.1 (32/64bit), Mandrake 10.0, 10.1 (32/64bit), Mandriva 2005, 2006, 2007, 2008, 2009 (32/64bit), Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10 (32/64bit), SuSE Linux Enterprise Desktop 9, 10 (32/64bit), Debian 3.1, 4.0, 5.0 (32/64bit)

Font Support

Windows/Mac/Linux fonts

Media Handling

Multipurpose Tray: 60 – 163 gsm; Media types: Plain paper, envelopes, transparencies, labels, cardstock, Pre-printed paper, coloured paper; Main Tray: 60 – 105 gsm; Media types: Plain paper

Operating Environment

Temperature: Storage: 0° to 35° C, Operating: 10° to 32° C; Humidity: 20% to 80%, Sound pressure levels: Printing: less than 50 dB(A), Standby: less than 26 dB(A), Warm-up time (from power on): As fast as 18 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz; Power consumption: Standby: 60 W, Printing: 360 W, Power save: 4.5 W

Dimensions (WxDxH)

360 x 389 x 230 mm; Weight: 7.46 kg; Package Dimensions (WxDxH): 438 x 470 x 325 mm

Certifications

Listed UL 60950-1/CSA C22.2 No. 60950-1, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC

What Comes In The Box

- Phaser 3155 / 3160 Printer
- Toner Cartridge (1,000 print capacity¹)
- Quick Installation Guide
- Software and Documentation CD (including User Manual)
- Worldwide Warranty Statement
- Power cord
- USB cable

Supplies

Standard-Capacity Toner Cartridge: 1,500 std. pages¹ 108R00908

High-Capacity Toner Cartridge: 2,500 std. pages¹ 108R00909

Supplies Recycling Programme

Consumables for the Phaser 3155 / 3160 are part of the Xerox Green World Alliance Supplies Recycling Programme. For more information, please visit the Green World Alliance website at

www.xerox.com/gwa

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.



For more information visit us at www.xerox.com/office

©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver® and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 1/14 316BR-011B